

Hose Type 4/2

Duralife Flex™



Applications







Waterblasting: Heat Exchanger Tube Cleaning
Hydraulics: Instrumentation Packages for Gauges, Pressure Testing for Valves, Tooling and Control Panels



Inner Core: Polyoxymethylene (POM)
Pressure Support: 2 layers of high-tensile steel wire
Outer Cover: Polyamide (PA)
Colour: green, other colours upon request
Temperature: -22°F to 140°F [-30°C to +60°C]

Ø ID	Ø OD	Working Pressure*)	Burst Pressure ¹)	Min. Bend Radius	Weight	Nipple Ø ID	Sleeve	Sleeve Ø OD
0,16 inch	0,31 inch	17.400 psi	43.500 psi	2,95 inch	0,074 lbs/ft	0,10 inch	10420101 carbon steel	0,40 inch
4,0 mm	8,0 mm	1.200 bar	3.000 bar	75 mm	0,110 kg/m	2,5 mm	10420105 AISI 316Ti	10,1 mm

Fittings: ID4, Series A and X

Description	Size	Material	Part Number	
HP fitting	1/4"x28UNF LH	AISI 316Ti	40420205A	
male fitting one piece waterblast	1/16"x27 NPTF	carbon steel	30420452X / 30420452/1X	
male fitting one piece waterblast	1/8"x27 NPTF	carbon steel	30420462X / 30420462/1X	
male fitting one piece waterblast	5/16"x24 UNF	carbon steel	30420601X / 30420452/1X	
male fitting	1/16"x27 NPTF	carbon steel	30420412A	
male fitting	1/8"x27 NPTF	carbon steel	30420542A	
male fitting	1/4"x18 NPTF	carbon steel	30420422A	
male fitting	G1/8"	carbon steel	30420302A	
male fitting flat seal nozzle type	G1/8"	carbon steel	30420382A	
male fitting	G1/4"	carbon steel	30420322A	
male fitting USIT®-Ring	G1/4"	carbon steel	30420351A	
male fitting	M7	carbon steel	30420042A	
male fitting flat seal nozzle type	M7	carbon steel	30420082A	
male fitting	M8	carbon steel	30420052A	
male fitting	M10x1	carbon steel	30420002A	
BSP female swivel	G1/4"	carbon steel carbon steel AISI 316Ti	20430302A swivel nut / 50540301 swivel nut / 50540305	
metric female swivel with O-Ring	M24x1.5	carbon steel	20420042A / 51360201	
Type M female swivel	9/16"x18 UNF	carbon steel carbon steel	20420642A swivel nut / 50540601	

---- Additional fittings are available upon request. ----

¹) Production related variations up to 5 % are possible

*) The safety factors between the burst pressure and the working pressure as well as the test pressure depend on the operating conditions. For gaseous media a safety factor of 1:6 is to be applied and the outer cover is to be pricked. The indicated working pressure refers to the hose only. Depending on the used fitting the permitted working pressure of a hose assembly can be less. We reserve our rights for changes without notice.

