

Hose Type 6/2WPPA



Applications

Oil and Gas: Chemical Injection, Gaseous Media Handling, Hydraulic Control, Methanol Injection, Nitrogen Service, Sub Sea Well Control

Inner Core: PVDF
Pressure Support: 4 layers of high-tensile steel wire
Outer Cover: Polyamide (PA)
Colour: dark green, other colours upon request
Temperature: -4°F to 176°F [-20°C to +80°C]



Ø ID	Ø OD	Working Pressure*)	Burst Pressure 1)	Min. Bend Radius	Weight	Nipple Ø ID	Sleeve	Sleeve Ø OD
0,25 inch	0,48 inch	13.260 psi	46.400 psi	5,91 inch	0,179 lbs/ft	0,16 inch	10630191W carbon steel	0,61 inch
6,3 mm	12,2 mm	915 bar	3.200 bar	150 mm	0,266 kg/m	4,0 mm	10630195W AISI 316Ti	15,4 mm

Fittings: ID6, Series A

Description	Size	Material	Part Number	
male fitting	1/8"x27 NPTF	carbon steel	30620411A	
male fitting	1/4"x18 NPTF	carbon steel	30620401A	
male fitting	1/4"x18 NPTF	AISI 316Ti	30620405A	
male fitting	3/8"x18 NPTF	carbon steel	30620451A	
male fitting	G1/8"	carbon steel	30620311A	
male fitting with 60° cone	G1/4"	carbon steel	30620341A	
male fitting for USIT®-Ring	G1/4"	carbon steel	30620391A	
male fitting DIN3852 T2 form A	G1/4"	carbon steel	30620301A	
male fitting flat seal nozzle type	G1/4"	carbon steel	30620381A	
male fitting with 60° cone	G3/8"	carbon steel	30620321A	
male fitting for USIT®-Ring	G3/8"	carbon steel	30620351A	
BSP female swivel	G1/4"	carbon steel	20620301A / 50540301	
BSP female swivel	G1/4"	AISI 316Ti	20620305A / 50540305	
metric female swivel with O-Ring	M18x1.5	carbon steel	20620241A / 50620201	
metric female swivel with O-Ring	M22x1.5	carbon steel carbon steel AISI 316Ti	20620211A swivel nut / 51060201 swivel nut / 51060205	
metric female swivel with O-Ring	M24x1.5	carbon steel	20620042A / 51360201	
Type M female swivel	9/16"x18 UNF	carbon steel	20620641A / 50540601	
Type M female swivel	9/16"x18 UNF	AISI 316Ti	20620645A / 50540605	
JIC female swivel	9/16"x18 UNF	AISI 316Ti	S20630615A / S5063615	
female fitting	1/4"x18 NPTF	carbon steel	30620441A	
metric female swivel	M14x1.5	carbon steel	20620101A / 50540101	
metric female swivel	M16x1.5	carbon steel	20620141A / 50620121	
metric female swivel	M16x1.5	AISI 316Ti	20620145A / 50620125	

----- Additional fittings are available upon request. -----

1)Production related variations up to 5 % are possible

*) The safety factors between the burst pressure and the working pressure as well as the test pressure depend on the operating conditions. For gaseous media a safety factor of 1:6 is to be applied and the outer cover is to be pricked. The indicated working pressure refers to the hose only. Depending on the used fitting the permitted working pressure of a hose assembly can be less. We reserve our rights for changes without notice.

