

Hose Type 8/2PPA



Applications

Oil and Gas: Chemical Injection, Gaseous Media Handling, Hydraulic Control, Methanol Injection, Nitrogen Service, Sub Sea Well Control

Inner Core: PVDF
Pressure Support: 2 layers of high-tensile steel wire
Outer Cover: Polyamide (PA)
Colour: dark green, other colours upon request
Temperature: -4°F to 176°F [-20°C to +80°C]



Ø ID	Ø OD	Working Pressure*)	Burst Pressure 1)	Min. Bend Radius	Weight	Nipple Ø ID	Sleeve	Sleeve Ø OD
0,32 inch	0,52 inch	8.260 psi	29.000 psi	11,81 inch	0,155 lbs/ft	0,22 inch	10820101 carbon steel	0,70 inch
8,1 mm	13,3 mm	570 bar	2.000 bar	300 mm	0,230 kg/m	5,5 mm		17,8 mm

Fittings: ID8, Series A and X

Description	Size	Material	Part Number	
male fitting one piece waterblast	1/4"x18 NPTF	carbon steel	30820461X / 30820441/1X	<p>male one piece fitting</p>
male fitting one piece waterblast	3/8"x18 NPTF	carbon steel	30820441X / 30820441/1X	
male fitting one piece waterblast	G1/4"	carbon steel	30820361X / 30820441/1X	
male fitting	1/4"x18 NPTF	carbon steel	30820411A	
male fitting	3/8"x18 NPTF	carbon steel	30820401A	
male fitting DIN3852 T2 form A	G1/4"	carbon steel	30820351A	
male fitting with 60° cone	G1/4"	carbon steel	30820321A	
male fitting flat seal nozzle type	G1/4"	carbon steel	30820381A	
male fitting DIN3852 T2 form A	G3/8"	carbon steel	30820341A	
male fitting with 60° cone	G3/8"	carbon steel	30820301A	
BSP female swivel	G3/8"	carbon steel	20820301A / 50860301	
metric female swivel with O-Ring	M20x1.5	carbon steel	20820201A / 50860201	
metric female swivel with O-Ring	M24x1.5	carbon steel	20820042A / 50820241	
Type M female swivel	3/4"x16 UNF	AISI 316Ti AISI 316Ti carbon steel	20820645A swivel nut / 50840605 swivel nut / 50840601	
JIC female swivel	9/16"x18 UNF	carbon steel	20820601A / 50820601	
JIC female swivel	9/16"x18 UNF	AISI 316 Ti carbon steel	20820605A swivel nut / 50820601	

----- Additional fittings are available upon request. -----

1) Production related variations up to 5 % are possible

*) The safety factors between the burst pressure and the working pressure as well as the test pressure depend on the operating conditions. For gaseous media a safety factor of 1:6 is to be applied and the outer cover is to be pricked. The indicated working pressure refers to the hose only. Depending on the used fitting the permitted working pressure of a hose assembly can be less. We reserve our rights for changes without notice.

